

# AI890

## Compact Product Suite hardware selector



The AI890 Analog Input Module has 8 channels. The module includes Intrinsic Safety protection components on each channel for connection to process equipment in hazardous areas without the need for additional external devices.

Each channel can be either a current input or power and monitor a two-wire process transmitter. The current input is for externally powered transmitters. The input voltage drop of the current input is typically 3 V, PTC included. The transmitter supply for each channel is able to provide at least 15 V at a 20 mA loop current to power Ex certified process transmitters and is limited to 23 mA in overload conditions. All eight channels are isolated from the ModuleBus and power supply in one group. Power to the input stages is converted from the 24 V on the power supply connections.

TU890 and TU891 Compact MTU can be used with this module and it enables two wire connection to the process devices without additional terminals. TU890 for Ex applications and TU 891 for non Ex applications.

## Features and benefits

- 8 channels for 0...20 mA or 4...20 mA, single ended unipolar inputs.
- 1 group of 8 channels isolated from ground.
- Power and monitor for Ex certified two-wire transmitters.
- Non energy-storing analog inputs for externally powered sources.

### General info

|                      |                       |
|----------------------|-----------------------|
| Article number       | 3BSC690071R1          |
| Type                 | Analog Input          |
| Signal specification | 0...20 mA             |
| Number of channels   | 8                     |
| Signal type          | Unipolar single ended |
| HART                 | No                    |
| SOE                  | No                    |
| Redundancy           | No                    |
| High integrity       | No                    |
| Intrinsic safety     | Yes                   |
| Mechanics            | S800                  |

| Detailed data                      |  |
|------------------------------------|--|
| Resolution                         | 12 bit                                     |
| Isolation                          | Group wise isolated from ground            |
| Under/over range                   | 0 / 22 mA                                  |
| Error                              | Max. 0.1%                                  |
| Temperature drift                  | Typ. 50 ppm/°C Max. 100 ppm/°C             |
| Input filter (rise time 0-90%)     | 75 ms                                      |
| Update cycle time                  | 5 ms                                       |
| Current limiting                   | Built in current limited transmitter power |
| CMRR, 50Hz, 60Hz                   | >80 dB                                     |
| NMRR, 50Hz, 60Hz                   | >20 dB                                     |
| Rated insulation voltage           | 50 V                                       |
| Dielectric test voltage            | 500 V a.c.                                 |
| Power dissipation                  | 1.5 W                                      |
| Current consumption +5 V Modulebus | Typ. 70 mA, Max. 150 mA                    |
| Current consumption +24 V external | Typ. 220 mA, Max. <300 mA                  |

| Diagnostics                      |   |
|----------------------------------|---|
| Front LED's                      | F(ault), R(un), W(arning)                   |
| Supervision                      | Internal process supply                     |
| Status indication of supervision | Module Error, Module Warning, Channel error |

| Environment and certification   |  |
|---------------------------------|--|
| CE mark                         | Yes  |
| Electrical safety               | EN 61010-1, EN 61010-2-201   |
| Hazardous Location              | ATEX/IECEx Zone 2 with interface to Zone 0, cFMus C1, Div 2/Zone 2 with interface to C1, C2, C3 Div 1/Zone 0 |
| Marine certification            | ABS, BV, DNV, LR   |
| Temperature, Operating          | 0 to +55 °C (+32 to +131 °F)   |
| Temperature, Storage            | -40 to +70 °C (-40 to +158 °F)   |
| Pollution degree                | Degree 2, IEC 60664-1  |
| Corrosion protection            | ISA-S71.04: G3   |
| Relative humidity               | 5 to 95 %, non-condensing  |
| Max ambient temperature         | 55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)  |
| Protection class                | IP20 according to IEC 60529  |
| Mechanical operating conditions | IEC/EN 61131-2   |
| EMC                             | EN 61000-6-4, EN 61000-6-2   |
| Overvoltage categories          | IEC/EN 60664-1, EN 50178   |
| Equipment class                 | Class I according to IEC 61140; (earth protected)  |
| RoHS compliance                 | DIRECTIVE/2011/65/EU (EN 50581:2012)   |
| WEEE compliance                 | DIRECTIVE/2012/19/EU   |

| Compatibility |              |
|---------------|--------------|
| Use with MTU  | TU890, TU891 |
| Keying code   | AC           |

| Dimensions |  |
|------------|--|
| Width      | 45 mm (1.77")                                      |
| Depth      | 102 mm (4.01"), 111 mm (4.37") including connector |
| Height     | 119 mm (4.7")                                      |
| Weight     | 0.2 kg (0.44 lbs.)                                 |



# Related products



TU890



TU891

---

**[solutions.abb/compactproductsuite](https://solutions.abb/compactproductsuite)  
[solutions.abb/controlsystems](https://solutions.abb/controlsystems)**

---

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved